

Journal: Physical Review Applied

Accession code: QT10022N

Article Title: Distributing Polarization-Entangled Photon Pairs with High Rate Over Long Distances through Standard Telecommunication Fiber

First Author: Lijiong Shen

Corresponding Author: Christian Kurtsiefer

AUTHOR QUERIES - TO BE ANSWERED BY THE CORRESPONDING AUTHOR

The following queries have arisen during the typesetting of your manuscript. Please answer these queries by marking the required corrections at the appropriate point in the text.

Q1	We have inserted a shortened title for the running head of your paper. Please confirm acceptance or provide an alternative.
Q2	Please provide missing country names for the affiliations 1 and 2.
Q3	Please note that spacing, hyphenation, and formatting have been standardized throughout to comply with journal style. Also, minor copyediting changes have been made throughout the paper to follow journal and grammar guidelines and to allow improved readability. Please check the redlined proof to ensure that your meaning has not been changed.
Q4	Please carefully check all formulas, display equations, spacing, punctuation, font style (such as italic, roman, and bold), accents, and special characters throughout, including in the Abstract and endnotes.
Q5	Please check the order and appearance for all parts of all figures. Also note that the figure labels have been adjusted so that the roman and italic characters match the main text. Please check and confirm that no errors have been introduced.

Important Notice to Authors

Attached is a PDF proof of your forthcoming article in Physical Review Applied. The article accession code is QT10022N. Your paper will be in the following section of the journal: RESEARCH ARTICLES

Please note that as part of the production process, APS converts all articles, regardless of their original source, into standardized XML that in turn is used to create the PDF and online versions of the article as well as to populate third-party systems such as Portico, Crossref, and Web of Science. We share our authors' high expectations for the fidelity of the conversion into XML and for the accuracy and appearance of the final, formatted PDF. This process works exceptionally well for the vast majority of articles; however, please check carefully all key elements of your PDF proof, particularly any equations or tables.

Figures submitted electronically as separate PostScript files containing color appear in color in the journal.

No further publication processing will occur until we receive your response to this proof.

ORCIDs

Please follow any ORCID links () after the authors' names and verify that they point to the appropriate record for each author. Requests to add ORCIDs should be sent no later than the first proof revisions. If authors do not subsequently add/authenticate ORCIDs within seven business days, production of the paper will proceed and no further requests to add ORCIDs will be processed. See complete details regarding ORCID requests and ORCID verification at <https://journals.aps.org/authors/adding-orcids-during-proof-corrections>.

NOTE: If this paper is an Erratum or a Reply, the corresponding author's ORCID may be present if previously provided to APS, but no ORCIDs can be added at proof stage.

Other Items to Check

- Please note that the original manuscript has been converted to XML prior to the creation of the PDF proof, as described above. Please carefully check all key elements of the paper, particularly the equations and tabular data.
- Title: Please check; be mindful that the title may have been changed during the peer review process.
- Author list: Please make sure all authors are presented, in the appropriate order, and that all names are spelled correctly.
- Please make sure you have inserted a byline footnote containing the email address for the corresponding author, if desired. Please note that this is not inserted automatically by this journal.
- Affiliations: Please check to be sure the institution names are spelled correctly and attributed to the appropriate author(s).
- Receipt date: Please confirm accuracy.
- Acknowledgments: Please be sure to appropriately acknowledge all funding sources.
- Hyphenation: Please note hyphens may have been inserted in word pairs that function as adjectives when they occur before a noun, as in “x-ray diffraction,” “4-mm-long gas cell,” and “*R*-matrix theory.” However, hyphens are deleted from word pairs when they are not used as adjectives before nouns, as in “emission by x rays,” “was 4 mm in length,” and “the *R* matrix is tested.” Note also that Physical Review follows U.S. English guidelines in that hyphens are not used after prefixes or before suffixes: superresolution, quasiequilibrium, nanoprecipitates, resonancelike, clockwise.
- Please check that your figures are accurate and sized properly. Make sure all labeling is sufficiently legible. Figure quality in this proof is representative of the quality to be used in the online journal. To achieve manageable file size for online delivery, some compression and downsampling of figures may have occurred. Fine details may have become somewhat fuzzy, especially in color figures. Figures to be published in color online will appear in color on these proofs if viewed on a color monitor or printed on a color printer.
- Overall, please proofread the entire formatted article very carefully. The redlined PDF should be used as a guide to see changes that were made during copyediting. However, note that some changes to math and/or layout may not be indicated.

Ways to Respond

- Web: If you accessed this proof online, follow the instructions on the web page to submit corrections.
- Email: Send corrections to apspmtteam@novatechset.com Include the accession code QT10022N in the subject line.

Distributing Polarization-Entangled Photon Pairs with High Rate Over Long Distances through Standard Telecommunication Fiber

Lijiong Shen¹,¹ Chang Hoong Chow¹,¹ Justin Yu Xiang Peh,¹ Xi Jie Yeo,¹ Peng Kian Tan,¹ and Christian Kurtsiefer^{1,2,*}

¹*Centre for Quantum Technologies, National University of Singapore, 3 Science Drive 2, Singapore 117543*

²*Department of Physics, National University of Singapore, 2 Science Drive 3, Singapore 117551*



(Received 6 June 2022; revised 27 July 2022; accepted 5 October 2022; published XX XX 2022)

Distributing entanglement through standard telecommunication fiber is particularly important for quantum key distribution protocols with low vulnerability over metropolitan distances. However, entanglement distribution over long distance through optical fiber so far could only be accomplished with moderate photon pair rates. In this work, we present entanglement distribution over 50 km of standard telecommunication fiber with a pair rate of more than $10\,000\text{ s}^{-1}$ using a bright nondegenerate photon pair source. Signal and idler wavelengths of this source are optimized for low dispersion in optical fiber and high efficiency for single-photon avalanche diode detectors, respectively. The resulting modest hardware requirement and high rate of detected entangled photon pairs could significantly enhance practical entanglement-based quantum key distribution in existing metropolitan fiber networks.

DOI: [10.1103/PhysRevApplied.0.XXXXXX](https://doi.org/10.1103/PhysRevApplied.0.XXXXXX)

I. INTRODUCTION

Quantum entanglement is one of the most fascinating phenomena in quantum physics. It provides the foundation for applications such as quantum teleportation, some variants of quantum key distribution (QKD) [1–4], or implementations of a quantum internet [5,6].

In recent years, the rapid development of quantum technologies has driven QKD towards higher key generation rates [7] and longer distances: metropolitan area [8,9], intercity [10], and even intercontinental quantum communication has been demonstrated recently [11]. Currently, building secure quantum networks on top of these point-to-point quantum communication schemes is of increasing interest in research and commercial applications [12].

Most implementations of QKD are based on prepare-and-measure protocols due to its optical simplicity. In contrast, entanglement-based QKD can offer the advantage of not requiring a trusted active random number generator [13], and is immune to photon number splitting attacks, exposing fewer vulnerabilities in a practical implementation [14]. Moreover, entanglement is also the basis of device-independent quantum cryptography, a class of higher-security QKD schemes that does not rely on the premise that the involved devices can be trusted [15,16]. Thus, it is highly desirable to distribute entanglement over long distance for future quantum secure networks.

While distributing entanglement over very long distance through free space [17] or even satellite links [18] is naturally appealing due to the low optical transmission loss in air, optical fibers can guide photons over the long distance without challenging alignments or environmental considerations. They also are the sole option when a line-of-sight is unavailable. Optical fibers are a particularly attractive transmission method in metropolitan areas, where ITU G.652D standard compliant fiber is likely already deployed as part of the existing telecommunication infrastructure [19].

Early work has demonstrated distribution of polarization-entangled photons through fiber over 1.45 km [20] for relatively short wavelengths. Polarization entanglement is much easier to prepare, measure, and couple to other physical systems compared with time-bin entanglement [21], which is a common encoding scheme at telecom wavelengths because it requires fewer expensive detectors. Time-bin entanglement is also less susceptible to polarization degradation due to polarization mode dispersion (PMD) in optical fibers, an effect that is severe for broadband photons found in many sources of polarization-entangled photons [22]. Improved technology continuously lowered the PMD of optical fibers, and permitted to manufacture low-loss optical filters to reduce photon bandwidth. Consequently, polarization entanglement distribution over tens or even more than 100 km optical fiber has been demonstrated in recent years [23–26].

However, these demonstrations had to make optimizations that limit their practicality. For example,

*christian.kurtsiefer@gmail.com

dispersion-shifted fibers (typically G.655 standard compliant fibers) have lower transmission losses and dispersion at 1550 nm compared with G.652D fibers [27], but are far less frequently deployed in existing telecommunication networks. Alternatively, chromatic dispersion and PMD could be reduced by using narrow band pass filters together with conventional entangled pair sources, but this reduces the heralding efficiency of photon pairs even for ideal spectral filters with unity transmission in pass band [28], eventually leading to a lower entangled photon pair detection rate. Consequently, most reported work on long distance entanglement distribution was carried out with photon pair rates that are too low for most practical applications. Similarly, superconducting nanowire single-photon detectors (SNSPDs) are used in many demonstrations of long-distance entanglement distribution due to their high efficiency, low dark counts, and low timing jitter [29]. However, SNSPDs need to be cooled below 4 K, which requires a significant overhead in power, size, and cost in comparison with typical single-photon avalanche photodiodes (APDs).

In this work, we present a highly nondegenerate entangled photon pair source based on type-0 spontaneous parametric down-conversion (SPDC) process to overcome these drawbacks in fiber-based entanglement distribution. One of the photons in pairs has a wavelength of 1310 nm and falls in the zero-dispersion window of G.652D standard compliant fiber, and a subnanometer bandwidth even without any spectral filtering. The other photon in the pairs has a wavelength around 586 nm where Si APDs have nearly optimal detection efficiency. With such a source, we observe an average entanglement visibility of more than 97% locally. After transmitting the 1310 nm photons through 50 km of G.652D compliant fiber, we still observe a photon pair coincidence rate over $10\,000\text{ s}^{-1}$ with a pair of APDs, with a raw polarization entanglement visibility of 92.5%. The corresponding estimated quantum key rate in a BBM-92-like protocol [4] with such a source would be 5172 s^{-1} . This is a significant boost in rates for practical quantum key distribution in a metropolitan area.

II. EXPERIMENTAL SETUP

A sketch of the experimental setup is shown in Fig. 1. Time-correlated photon pairs are generated via SPDC in a periodically poled potassium titanyl phosphate crystal (PPKTP, $2 \times 1 \times 20\text{ mm}^3$) that is pumped with light from a grating-stabilized diode laser at a wavelength of 405 nm. An α -BBO crystal splits the pump light into two paths of orthogonal polarizations (horizontal, H , and vertical, V) with a beam separation of 1 mm through birefringence. A half-wave plate (HWP) transforms the H polarized pump light part back to V . The type-0 SPDC process in both conversion paths generates photon pairs in a state $|VV\rangle$, which then are separated by wavelength using a dichroic mirror.




FIG. 1. Schematic of the nondegenerate entangled photon pair source. Pump light at 405 nm is split into two paths and is subject to type-0 SPDC inside the PPKTP crystal. The polarization state in the upper path is rotated by 90° by a half-wave plate. Each pump path generates photon pairs with a nondegenerate wavelength at 1310 nm (signal) and 586 nm (idler). A dichroic mirror (DM) separates the nondegenerate photons from both pump paths. A pair of α -BBO crystals recombine the two signal and two idler paths separately to create an entangled state $|\Phi^-\rangle = (1/\sqrt{2})(|HH\rangle - |VV\rangle)$. A motorized HWP and a PBS projects idler photons into different polarizations. Signal photons at 1310 nm are first coupled into a long SMF28e+ telecommunication fiber before projection into linear bases in a similar way as the idler photons.

The polarization of the separated signal and idler photons from one of the pump paths is transformed to horizontal by two HWPs designed for their respective wavelengths. With this, the crystal generates $|VV\rangle$ and $|HH\rangle$ photon pairs in the different pump paths of the same crystal, which are then spatially overlapped by two α -BBO crystal beam splitters, one in each collection path to take care of the different birefringent properties at signal and idler wavelengths. The entanglement of photons arises from the indistinguishability between the photon pairs generated in the two down-conversion paths [30,31]. By adjusting the relative power and phase between the two pump paths, the maximally entangled state

$$|\Phi^-\rangle = \frac{1}{\sqrt{2}}(|HH\rangle - |VV\rangle)$$

can be prepared.

Both a long-pass (LP) filter with a cutoff wavelength at 1200 nm and a bandpass (BP) filter with a bandwidth of 20 nm centered at 586 nm effectively remove pump light from the individual collection path. A timestamp unit records the photon arrival time on both InGaAs APD (timing jitter $\approx 250\text{ ps}$) and Si APD (timing jitter $\approx 500\text{ ps}$) to look for coincidences. We choose a coincidence window of 1.25 ns to capture the majority of the photon pairs for all the measurements reported in this work.

The pair generation rate of the source is first characterized without the entanglement mechanism mediated by the

beam displacers. At a pump power of $100\ \mu\text{W}$, a pair rate of more than $10\,000\ \text{s}^{-1}$ is observed with over 20% heralding efficiency; this value increases to 22% after correction for detector dark counts and after pulses. It is worth noting that even with a relatively optimistic estimation of the detector efficiency (60% for the Si APD and 15% for the InGaAs APD), the ideal heralding efficiency assuming a perfect fiber coupling while ignoring losses on multiple optical elements is predicted to be $\sqrt{(15\% \times 60\%)} = 30\%$ (see Appendix A). This implies a close to optimal collection efficiency. The single rate at the Si APD exceeds $70\,000\ \text{s}^{-1}$ with a pump power of $100\ \mu\text{W}$. Assuming a Si APD efficiency of 60%, we can safely infer that at a pump power of 1 mW, the source should generate more than 1 million photon pairs in a second; a direct measurement would have severely saturated the available detectors.

Figure 2(a) shows a spectrum of the signal photons recorded with a grating spectrometer, with only a single peak in a range of 300 nm, with a center wavelength of

1310.12 nm and a full width at half maximum (FWHM) of 0.84 nm obtained from a fit to a Gaussian distribution. The spectrometer resolution is separately determined to be 0.47 nm (FWHM) with a distributed feedback laser at 1310 nm and a bandwidth of 3 MHz. Thus, the deconvoluted bandwidth of the source signal photons at 1310 nm is around 0.7 nm, corresponding to 120 GHz. Figure 2(b) shows the change of the center wavelength of signal photons with the temperature of the PPKTP crystal. The wavelength increases almost linearly with a slope of 0.8 nm/K over the zero-dispersion range (1304–1324 nm) of the SMF28e+, G652D-compliant fiber.

To experimentally verify the zero-dispersion property of the fiber on signal photons, we carried out a coincidence measurement on photon pairs from the source with and without the 50-km fiber. For better timing resolution, the Si APD was replaced with a device with smaller timing jitter ($<40\ \text{ps}$) but lower detector efficiency (40%). The coincidence peak is shifted by around $247\ \mu\text{s}$ for the measurement with the 50-km fiber. Both coincidence measurements are normalized to their maximum coincidence rate for easier visual comparison. Figure 2(c) clearly shows that the dispersion is unnoticeable even with the fast Si APD.

III. ENTANGLEMENT DISTRIBUTION

The entanglement quality measurements were first carried out locally with the three α -BBO beam displacer inserted in the source, and polarization projections in signal and idler paths are implemented as shown in Fig. 1. To characterize entanglement, we extracted the visibility of polarization correlations in different bases, details are explained in Appendix B. The additional optics slightly reduces the source heralding efficiency from 22% to 18% for both pump paths. At $380\text{-}\mu\text{W}$ pump power, a raw visibility of $99.7 \pm 0.1\%$ for the horizontal/vertical (H/V) basis, and $95.5 \pm 0.1\%$ for the diagonal/antidiagonal (D/A) basis is measured without 50-km delay fiber, resulting in an average raw visibility of $97.6 \pm 0.1\%$ ($97.8 \pm 0.1\%$ after correcting for background coincidences, see Appendix C). The corresponding coincidence rate averaged over H/V and D/A bases is $13\,012 \pm 14\ \text{s}^{-1}$.

Then, the 50-km SMF28e+ fiber ($-17\ \text{dB}$ loss) is inserted between the source and the polarization analyzer on the signal branch. The observed coincidence rates and visibilities for different pump powers are shown in Fig. 3. As expected, the coincidence rate increases mostly linearly with pump power. We attribute the small nonlinearity at 15 mW pump power to an onset of saturation of the Si APD (at a detection rate of $3.8 \times 10^6\ \text{s}^{-1}$; specified maximum count rate $3 \times 10^7\ \text{s}^{-1}$). The raw average visibility of the polarization correlation decreases with the pump power due to the quadratically increasing background coincidence (lower panel). However, after correcting the visibility for




FIG. 2. (a) The spectrum of signal photons from the nondegenerate pair source at a temperature of $33.4\ ^{\circ}\text{C}$ of the PPKTP crystal shows a single peak around 1310 nm with a nearly Gaussian profile (see fit to the data in the inset). (b) Signal photon wavelength dependence on PPKTP temperature. (c) Time correlation of photon detection events from a pair of APDs, with the signal photon passing through 0 and 50 km of SMF28e+ fiber, respectively. The temporal correlations for the 50 km transmission case are offset and normalized for visual comparison. Both histograms show a nearly indistinguishable distribution with a full width at half maximum around 280 ps.




FIG. 3. (a) Average pair rates for different pump powers. The locally collected photon pair rate, averaged over H/V and D/A bases, is $13\,012 \pm 14\text{ s}^{-1}$ at $380\text{ }\mu\text{W}$ pump power. Pair rates with the 50-km fiber in the signal arm are $1606 \pm 3\text{ s}^{-1}$, $4686 \pm 6\text{ s}^{-1}$, $8033 \pm 10\text{ s}^{-1}$, and $10\,033 \pm 16\text{ s}^{-1}$ at their corresponding pump powers. (b) Visibility of polarization correlations as a measure of entanglement quality for different pump powers. The raw visibility observed locally with $380\text{ }\mu\text{W}$ pump is $97.6 \pm 0.1\%$. After propagating through 50 km of SMF28e+ fiber, the raw visibility reduces to $96.5 \pm 0.1\%$, $95.4 \pm 0.1\%$, $94.5 \pm 0.1\%$, and $92.5 \pm 0.1\%$ for a respective pump power of 2, 6, 11, and 15 mW. Background-corrected visibilities range from 97% to 98% for all the measurements.

background coincidences, the visibility of polarization correlations and, hence, the quality of entanglement remains at an almost constant high level with no strong dependence on the pump power.




FIG. 4. Polarization correlations in both H/V and D/A bases measured at 15-mW pump power after transmission of the signal photons through 50 km of SMF28e+ fiber. The coincidence rate is measured with polarization optics before signal and idler photon detection, as shown in Fig. 1. The polarization on the idler side is kept at one of the four linear settings (H, V, D, and A) whereas the polarization on signal side is rotated over 360° using the half-wave plate.

The raw visibility at 15 mW pump power is $94.0 \pm 0.1\%$ in the H/V basis, and $91.0 \pm 0.2\%$ in the D/A basis, corresponding to an average visibility of $92.5 \pm 0.1\%$ (see Fig. 4). After correction for background coincidences, the average visibility at 15-mW pump power reaches $97.1 \pm 0.1\%$. The pair rate averaged over H/V and D/A bases is $10\,033 \pm 16\text{ s}^{-1}$. Assuming that the measurement basis is chosen randomly and uniformly, that noise parameters are independent of measurement settings, and using a realistic bidirectional error correction efficiency value of 1.1 [32,33], the estimated key distribution rate in a BBM-92 protocol would be 5172 s^{-1} .

IV. CONCLUSION

We present an entangled photon-pair source that is suitable for long distance quantum communication over the most deployed optical fiber compliant with the G.652D standard. The pair source generates signal photons at the zero-dispersion wavelength (1310 nm), whereas the corresponding idler photons have a wavelength of 586 nm, which is close to the optimal efficiency of typical Si APDs. Notably, the wavelength of the idler photon can be easily shifted slightly to be resonant with transitions in $^{151}\text{Eu}^{3+}:\text{Y}_2\text{SiO}_5$ (580 nm) or Sodium atoms (589 nm) by temperature-tuning the nonlinear crystal or frequency-tuning the pump light to interface with commonly used stationary quantum nodes.

The source has a brightness of more than 10^6 pairs/s/mW. With the close to ideal mode matching that can be accomplished with it, more than $10\,000\text{ s}^{-1}$ pairs are observed locally at $100\text{ }\mu\text{W}$ pump power using a pair of APDs. Entangled photon pairs can be generated by beam-displacement interferometer with minimal loss in brightness, and show a visibility of polarization correlations of over 97%.

The low intrinsic bandwidth of 0.7 nm of signal photons in the conversion process strongly suppresses temporal dispersion of photons passing through 50 km of SMF28e+, G652D-compliant optical fiber, and permits the use of a narrow coincidence time window which helps to reject accidental coincidences that would deteriorate the observable entanglement quality. At the same time, an entangled photon pair rate of more than $10\,000\text{ s}^{-1}$ with the same fiber can be detected with relatively simple APDs. With the usual error correction methods, this source/detection combination can be used to generate a secure bit rate of more than 5000 s^{-1} in a BBM-92 protocol using simple polarization encoding [32,33]. With the presented source, entanglement distribution can easily be extended to distances beyond 100 km at a rate of hundreds of pairs/second, without switching to more sophisticated superconducting single-photon detectors. To our knowledge, the entangled pair rate is at least an order of magnitude higher than other pair sources over the similar

distance [23–25], despite the larger fiber attenuation per unit length in the O band compared with the C band. Moreover, QKD applications using photons in the O band have the advantage in that the quantum signal can copropagate with light of classical internet traffic in C band over the same fiber link [34]. We therefore believe that such a source can significantly improve entanglement distribution over metropolitan distances, permitting an integration of high-rate entanglement-based quantum key distribution into existing telecommunication network with realistic detection devices.

ACKNOWLEDGMENTS

This work has been financially supported by the Quantum Engineering Programme through QEP-P1: Superconducting Nanowire and NRF2021-QEP2-04-P01: National Quantum-Safe Network, as well as the Ministry of Education and the National Research Foundation, Prime Minister's Office, Singapore.

APPENDIX A: HERALDING EFFICIENCY

Assuming a photon pair production rate P in the down-conversion crystal, single-photon detectors with efficiencies η_1 and η_2 will report single-photon rates $S_{1(2)} = P\eta_{1(2)}$, where $\eta_{1,2}$ are total efficiencies, which include optical transmission, collection efficiencies through mode matching, and detection efficiencies of the single-photon detectors. A coincidence is registered when a photodetection event from each detector fall in a coincidence window τ_c . With negligible accidental coincidences, a coincidence rate $C = P\eta_1\eta_2$ can be observed.

The heralding efficiency η of the photon pair is defined as the pair to singles ratio [35] $C/\sqrt{S_1S_2}$. Substituting coincidence and single rates with the above expressions leads to $\eta = \sqrt{\eta_1\eta_2}$. Assuming ideal mode matching without any transmission loss, the total efficiency $\eta_{1(2)}$ in each collection path is just the corresponding detector efficiency.

APPENDIX B: VISIBILITY MEASUREMENT

A combination of a HWP and a PBS ($T_p:T_s > 1000:1$) projects the polarization before coupling into the spatial mode selection fiber for the idler photon (586 nm). A similar free-space polarization measurement scheme is used for signal photons, where an additional quarter-wave plate (QWP) is used to remove the ellipticity after fiber passage; in this path, polarization elements HWP and PBS are also placed behind the long fiber. On the idler side, four different polarizations (horizontal, H; vertical, V; diagonal, D; and antidiagonal, A) are chosen by setting the HWP accordingly. On the signal side, the orientation of the linear polarization is changed in finer steps




FIG. 5. Correlation of photon detection events from a pair of APDs for entanglement distribution, with the signal photon passing through 50 km of SMF28e+ fiber. The horizontal axis for the time difference is offset by about 247 μ s. We consider detection events as coincidences when they fall into the time interval τ_c (width: 1.25 ns), and measure the coincidence rate in a time window τ_{acc} of the same width, displaced by about 7 ns.

by rotating the HWP to obtain a visibility of the polarization correlations via $V = (C_{\max} - C_{\min})/(C_{\max} + C_{\min})$, where $C_{\max}$ and $C_{\min}$ are extracted from a sinusoidal fit to polarization correlations shown in Fig. 4.

The source reported here shows a visibility close to 100% in H/V basis, and a slightly lower visibility in D/A basis. We attribute this to the chromatic dispersion caused by the α -BBO displacement crystal: the dispersion leads to a variation of the phase ϕ of the entangled state $|\Phi^-\rangle = (1/\sqrt{2})(|HH\rangle - e^{i\phi}|VV\rangle)$ for different frequency components of the down-converted photons, lowering the overall visibility in the D/A basis.

APPENDIX C: BACKGROUND CORRECTION

Apart from coincidences that can be attributed to photon pairs from the same SPDC process, we detect accidental coincidences from different pair generation processes, or from other detection processes. We estimate this accidental coincidence rate C_{acc} by recording the coincidence rate for time differences displaced by 7 ns from the main coincidence time window (see Fig. 5). Then, the coincidence rates are corrected by subtracting their respective accidental coincidence rate C_{acc} at each HWP angle. The corrected visibility is evaluated as $V = (C_{\max}^{corr} - C_{\min}^{corr})/(C_{\max}^{corr} + C_{\min}^{corr})$. The $C_{\max}^{corr}$ and $C_{\min}^{corr}$ are also extracted from a sinusoidal fit to the corrected polarization correlations.

- [1] C. H. Bennett, G. Brassard, C. Crépeau, R. Jozsa, A. Peres, and W. K. Wootters, Teleporting an Unknown Quantum

- State via Dual Classical and Einstein-Podolsky-Rosen Channels, *Phys. Rev. Lett.* **70**, 1895 (1993).
- [2] C. H. Bennett and G. Brassard, Quantum cryptography: Public key distribution and coin tossing, *Proc. IEEE Int. Conf. Comput. Syst. Signal Process.* **560**, 175 (1984).
- [3] A. K. Ekert, Quantum Cryptography Based on Bell's Theorem, *Phys. Rev. Lett.* **67**, 661 (1991).
- [4] C. H. Bennett, G. Brassard, and N. D. Mermin, Quantum Cryptography Without Bell's Theorem, *Phys. Rev. Lett.* **68**, 557 (1992).
- [5] H. J. Kimble, The quantum internet, *Nature* **453**, 1023 (2008).
- [6] M. Pompili, S. L. Hermans, S. Baier, H. K. Beukers, P. C. Humphreys, R. N. Schouten, R. F. Vermeulen, M. J. Tiggeleman, L. dos Santos Martins, B. Dirkse, *et al.*, Realization of a multinode quantum network of remote solid-state qubits, *Science* **372**, 259 (2021).
- [7] R. I. Woodward, Y. Lo, M. Pittaluga, M. Minder, T. Paraíso, M. Lucamarini, Z. Yuan, and A. Shields, Gigahertz measurement-device-independent quantum key distribution using directly modulated lasers, *Npj Quantum Inf.* **7**, 1 (2021).
- [8] Y.-L. Tang, H.-L. Yin, Q. Zhao, H. Liu, X.-X. Sun, M.-Q. Huang, W.-J. Zhang, S.-J. Chen, L. Zhang, L.-X. You, Z. Wang, Y. Liu, C.-Y. Lu, X. Jiang, X. Ma, Q. Zhang, T.-Y. Chen, and J.-W. Pan, Measurement-device-independent quantum key distribution over untrusted metropolitan network, *Phys. Rev. X* **6**, 011024 (2016).
- [9] Y. Shi, S. Moe Thar, H. S. Poh, J. A. Grieve, C. Kurtsiefer, and A. Ling, Stable polarization entanglement based quantum key distribution over a deployed metropolitan fiber, *Appl. Phys. Lett.* **117**, 124002 (2020).
- [10] J.-P. Chen, C. Zhang, Y. Liu, C. Jiang, W.-J. Zhang, Z.-Y. Han, S.-Z. Ma, X.-L. Hu, Y.-H. Li, H. Liu, *et al.*, Twin-field quantum key distribution over a 511 km optical fibre linking two distant metropolitan areas, *Nat. Photonics* **15**, 570 (2021).
- [11] S.-K. Liao, *et al.*, Satellite-Relayed Intercontinental Quantum Network, *Phys. Rev. Lett.* **120**, 030501 (2018).
- [12] Y. A. Chen, Q. Zhang, T. Y. Chen, W. Q. Cai, S. K. Liao, J. Zhang, K. Chen, J. Yin, J. G. Ren, Z. Chen, *et al.*, An integrated space-to-ground quantum communication network over 4,600 kilometres, *Nature* **589**, 214 (2021).
- [13] I. Marcikic, A. Lamas-Linares, and C. Kurtsiefer, Free-space quantum key distribution with entangled photons, *Appl. Phys. Lett.* **89**, 101122 (2006).
- [14] N. Lütkenhaus, Security against individual attacks for realistic quantum key distribution, *Phys. Rev. A* **61**, 052304 (2000).
- [15] A. Acín, N. Brunner, N. Gisin, S. Massar, S. Pironio, and V. Scarani, Device-Independent Security of Quantum Cryptography Against Collective Attacks, *Phys. Rev. Lett.* **98**, 230501 (2007).
- [16] V. Scarani, H. Bechmann-Pasquinucci, N. J. Cerf, M. Dušek, N. Lütkenhaus, and M. Peev, The security of practical quantum key distribution, *Rev. Mod. Phys.* **81**, 1301 (2009).
- [17] J. Yin, J. G. Ren, H. Lu, Y. Cao, H. L. Yong, Y. P. Wu, C. Liu, S. K. Liao, F. Zhou, Y. Jiang, *et al.*, Quantum teleportation and entanglement distribution over 100-kilometre free-space channels, *Nature* **488**, 185 (2012).
- [18] J. Yin, Y. Cao, Y. H. Li, S. K. Liao, L. Zhang, J. G. Ren, W. Q. Cai, W. Y. Liu, B. Li, H. Dai, *et al.*, Satellite-based entanglement distribution over 1200 kilometers, *Science* **356**, 1140 (2017).
- [19] S. Wang, W. Chen, Z.-Q. Yin, H.-W. Li, D.-Y. He, Y.-H. Li, Z. Zhou, X.-T. Song, F.-Y. Li, D. Wang, *et al.*, Field and long-term demonstration of a wide area quantum key distribution network, *Opt. Express* **22**, 21739 (2014).
- [20] A. Poppe, A. Fedrizzi, R. Ursin, H. R. Böhm, T. Lorünser, O. Maurhardt, M. Peev, M. Suda, C. Kurtsiefer, H. Weinfurter, T. Jennewein, and A. Zeilinger, Practical quantum key distribution with polarization entangled photons, *Opt. Express* **12**, 3865 (2004).
- [21] I. Marcikic, H. de Riedmatten, W. Tittel, H. Zbinden, M. Legré, and N. Gisin, Distribution of Time-Bin Entangled Qubits over 50 km of Optical Fiber, *Phys. Rev. Lett.* **93**, 180502 (2004).
- [22] G. Ribordy, J. Brendel, J.-D. Gauthier, N. Gisin, and H. Zbinden, Long-distance entanglement-based quantum key distribution, *Phys. Rev. A* **63**, 012309 (2000).
- [23] H. Hübel, M. R. Vanner, T. Lederer, B. Blauensteiner, T. Lorünser, A. Poppe, and A. Zeilinger, High-fidelity transmission of polarization encoded qubits from an entangled source over 100 km of fiber, *Opt. Express* **15**, 7853 (2007).
- [24] A. Treiber, A. Poppe, M. Hentschel, D. Ferrini, T. Lorünser, E. Querasser, T. Matyus, H. Hübel, and A. Zeilinger, A fully automated entanglement-based quantum cryptography system for telecom fiber networks, *New J. Phys.* **11**, 045013 (2009).
- [25] S. Wengerowsky, S. K. Joshi, F. Steinlechner, J. R. Zichi, S. M. Dobrovolskiy, R. van der Molen, J. W. Los, V. Zwiller, M. A. Versteegh, A. Mura, *et al.*, Entanglement distribution over a 96-km-long submarine optical fiber, *Proc. Natl. Acad. Sci. U.S.A.* **116**, 6684 (2019).
- [26] S. Wengerowsky, S. K. Joshi, F. Steinlechner, J. R. Zichi, B. Liu, T. Scheidl, S. M. Dobrovolskiy, R. v. d. Molen, J. W. Los, V. Zwiller, *et al.*, Passively stable distribution of polarisation entanglement over 192 km of deployed optical fibre, *Npj Quantum Inf.* **6**, 1 (2020).
- [27] C. Inc., Corning® LEAF® Optical Fiber Product Information (2019).
- [28] E. Meyer-Scott, N. Montaut, J. Tiedau, L. Sansoni, H. Herrmann, T. J. Bartley, and C. Silberhorn, Limits on the heralding efficiencies and spectral purities of spectrally filtered single photons from photon-pair sources, *Phys. Rev. A* **95**, 061803(R) (2017).
- [29] C. M. Natarajan, M. G. Tanner, and R. H. Hadfield, Superconducting nanowire single-photon detectors: physics and applications, *Supercond. Sci. Technol.* **25**, 063001 (2012).
- [30] M. Fiorentino and R. G. Beausoleil, Compact sources of polarization-entangled photons, *Opt. Express* **16**, 20149 (2008).
- [31] A. Lohrmann, C. Perumangatt, A. Villar, and A. Ling, Broadband pumped polarization entangled photon-pair source in a linear beam displacement interferometer, *Appl. Phys. Lett.* **116**, 021101 (2020).
- [32] X. Ma, C.-H. F. Fung, and H.-K. Lo, Quantum key distribution with entangled photon sources, *Phys. Rev. A* **76**, 012307 (2007).

- 455 [33] S. P. Neumann, T. Scheidl, M. Selimovic, M. Pivoluska, Quantum key distribution integrating with ultra-high-power 461
456 B. Liu, M. Bohmann, and R. Ursin, Model for optimizing classical optical communications based on ultra-low-loss 462
457 quantum key distribution with continuous-wave pumped fiber, *Opt. Lett.* **46**, 6099 (2021). 463
458 entangled-photon sources, *Phys. Rev. A* **104**, 022406 464
459 (2021). [35] A. Joobeur, B. E. A. Saleh, and M. C. Teich, Spatiotempo- 465
460 [34] J.-Q. Geng, G.-J. Fan-Yuan, S. Wang, Q.-F. Zhang, W. ral coherence properties of entangled light beams generated 466
Chen, Z.-Q. Yin, D.-Y. He, G.-C. Guo, and Z.-F. Han, by parametric down-conversion, *Phys. Rev. A* **50**, 3349 467
(1994).